



Canon C500 MK II Uncompressed Output Terminals

Sensor Mode	CFexpress Recording (x2)			12G-SDI output YCC422 10-bit	HDMI output YCC422 10-bit	MON. output YCC422 10-bit	
	Format	Signal	Resolution	Resolution	Resolution	Resolution	
FF 5.9K	Cinema RAW Light	RAW 12-bit / 10-bit	5.9K DCI	4096x2160p	4096x2160p / 1920x1080p 1920x1080i / 1280x720p	2048x1080p / 1920x1080p 1920x1080i / 1280x720p	
	XF-AVC	ALL-I	YCC422 10-bit				4K DCI
				4K UHD	3840x2160p	3840x2160p / 1920x1080p 1920x1080i / 1280x720p	1920x1080p / 1920x1080i 1280x720p
				2K DCI	2048x1080p	1920x1080p / 1920x1080i 1280x720p	2048x1080p / 1920x1080p 1920x1080i / 1280x720p
				FHD	1920x1080p		1920x1080p / 1920x1080i 1280x720p
	FHD interlace	1920x1080i	1920x1080i	1920x1080i			
Super 35	Cinema RAW Light	RAW 12-bit / 10-bit	4K DCI	4096x2160p	4096x2160p / 1920x1080p 1920x1080i / 1280x720p	2048x1080p / 1920x1080p 1920x1080i / 1280x720p	
	XF-AVC	ALL-I	YCC422 10-bit				4K DCI
				4K UHD	3840x2160p	3840x2160p / 1920x1080p 1920x1080i / 1280x720p	1920x1080p / 1920x1080i 1280x720p
				2K DCI	2048x1080p	1920x1080p / 1920x1080i 1280x720p	2048x1080p / 1920x1080p 1920x1080i / 1280x720p
				FHD	1920x1080p		1920x1080p / 1920x1080i 1280x720p
	FHD interlace	1920x1080i	1920x1080i	1920x1080i			
Super 16	Cinema RAW Light	RAW 12-bit / 10-bit	2K DCI	2048x1080p	1920x1080p / 1920x1080i 1280x720p	2048x1080p / 1920x1080p 1920x1080i / 1280x720p	
	XF-AVC	ALL-I	YCC422 10-bit				2K DCI
				FHD	1920x1080p	1920x1080p / 1920x1080i 1280x720p	
				FHD interlace	1920x1080i	1920x1080i	

SDI & HDMI out maximum resolution 4096x2160p. MON out maximum resolution 2048x1020p. HDMI Terminal and MON. terminal cannot output simultaneously.