



Sony PMW-F5 Specifications

Model	Sony PMW-F5
Sensor	35mm with Rolling Shutter
Lens Mount	FZ-Mount with PL Adaptor
Recording Formats	RAW 16-bit XAVC 10-bit 4:2:2 XAVC Class480 10-bit 4:2:2 XAVC Class300 10-bit 4:2:2 MPEG-4 SStP 8-bit 4:4:4/4:2:2 MPEG-2 8-bit 4:2:2
File Format	MXF
Resolution	RAW 4K: 4096x2160 (with additional AXS-R5 Recorder) RAW 2K: 2048x1080 (with additional AXS-R5 Recorder) XAVC 2K: 2048x1080 XAVC HD: 1920x1080 XAVC HD: 1920x1080 (Proxy when recording RAW) MPEG4 SStP: 1920x1080 MPEG2 HD: 1920x1080 MPEG2: 1280x720
Maximum Frame Rate*	RAW 4K: 50 fps (with additional AXS-R5 Recorder) RAW 2K: 240 fps (with additional AXS-R5 Recorder) XAVC 2K: 100 fps XAVC HD: 100 fps
Media	RAW: AXS (with additional AXS-R5 Recorder) Internal Recording: SxS Pro+ Setup/LUT: SD Card
Audio Recording Format	LPCM 8CH 24-bit 48-kHz
ISO	ISO Range: 800-6400 Native ISO: 2000
Internal ND Filters	Clear IRND 0.9 (3 Stops) IRND 1.8 (6 Stops)
Batteries	V-Lock
Inputs	2x XLR 3-Pin (Audio) 1x XLR 4-Pin (DC) 1x Digital Viewfinder Interface

	1x BNC (Genlock) 1x Timecode I/O
Outputs	4x BNC (HD: SDI 1/2 Line Output, SDI 3/4 Monitor Output) (4K: SDI 1/2/3/4 Line Output) 1x BNC (Test Output) 1x BNC (Shutter) 1x HDMI 1x Stereo Mini Jack (Headphone) 2x 12V Hirose (with v-lock adaptor plate)
Weight	2.2 kg (body only) 4.5 kg (with accessories**)

*PAL format

**Including camera body, body cap, EVF with cable, V-Lock battery plate, Vocas shoulder base plate, cage